

JUMBO SPRAY TILE



SUZUKA TEXTURE COATING

TAIWAN • MALAYSIA • THAILAND

Singapore Offices 62 Ubi Road 1, Oxley Bizhub 2, #01-41, Singapore 408734
20 Depot Lane #01-05, Singapore 109763
t. +65 6926 2610 m. +65 8788 6890 (WhatsApp only)

Malaysia Offices Unit A-01-24, Plaza Bukit Jalil (Aurora Place), No. 1, Persiaran Jalil 1, Bandar Bukit Jalil,
57000 Kuala Lumpur Malaysia
JB1:
6 Jalan Ekoperniagaan 1/28, Taman Ekoperniagaan, 81100 Johor Bahru, Johor, Malaysia
JB2:
27 Jalan Ekoperniagaan 2/7, Taman Ekoperniagaan, 81100 Johor Bahru, Johor, Malaysia
t. +60 7511 4788 m. +60 11 7019 0428 (WhatsApp only)



  [suzuka.group](#)



JUMBO SPRAY TILE



SPECIFICATION & METHOD STATEMENT

OUTLINE OF APPLICATION

Process	Material	Mixing (Weight Ratio)	Number Of Coat	Interval Time To Proceed Next Process (Hrs)	Consumption	Tools Of Application	
1	Surface Preparation	Surface shall be dry and free from dirt, oil, grease and foreign matters. Surface unevenness, crack and pin hole shall be treated with cement filler.					
2	Under Coating	EM Sealer : Water	100 : 0-2	1	3	0.15 - 0.20ltr/m ²	Roller or Brush
3	Texture Coating	Jumbo Tile : Water	100 : 0-5	1	24	1.0 - 1.6kg/m ²	Spray Gun
4	Top Coating	Acrylic Emulsion : Water	100 : 0-2	2	-	0.32 - 0.48ltr/m ²	Roller or Brush

JUMBO SPRAY TILE



JUMBO-HEAD CUT WITH PU COATING (L)



JUMBO-HEAD CUT (L)



JUMBO-HEAD CUT (L)



JUMBO-HEAD CUT (M)



JUMBO-HEAD CUT (S)



JUMBO-NORMAL (L)



JUMBO-NORMAL (M)



JUMBO-NORMAL (S)